

# Enterprise Tile

**New!**

1. Charcoal Only

## Specifications

Construction	Non woven high low structured loop dirt pocket pattern
Fiber Content	100% solution dyed polypropylene
Pile Weight	57 oz. per s/y
Total Weight	169 oz. per s/y
Backing	Bitumen or TacFast
Thickness	.50"
Tile size	19.69" x 19.69"
1 carton	12 tiles   or 32.5 sq.ft.
Wear Warranty	7 years on flat surfaces
Electrostatic Propensity	Permanently anti-static
Flammability Rating	(See below)
Radiant Panel Test - ASTM E648	Passes federal flamm. standard
Pill Test - ASTM D28259	Pass
Hot Metal Nut Test - BS4790/BS5287	Pass
LEED	May contribute towards MRC 4, IEQ 4.1, 5



**New!**

# Cross Stitch Tile

1. Charcoal Only

## Specifications

Construction	Non woven designer corduroy pattern
Fiber Content	100% solution dyed polypropylene
Pile Weight	65 oz. per s/y
Total Weight	175 oz. per s/y
Backing	Bitumen or TacFast
Thickness	.50"
Tile Size	19.69" x 19.69"
1 Carton	12 tiles   32.5 sq. ft.
Wear Warranty	7 years on flat surfaces
Electrostatic Propensity	Permanently anti-static
Flammability Rating	(See below)
Radiant Panel Test - ASTM E648	Passes federal flamm. standard
Pill Test - ASTM D28259	Pass
Hot Metal Nut Test - BS4790/BS5287	Pass
LEED	May contribute towards MRC 4, IEQ 4.1, 5

